

## Specifications of P4mm Indoor black LED Display

Pixel pitch	4mm	Size of pixel	2.5mm (circle)
Size of module	240mmmm×240mm	Pixel of module	60 ×60
Size of cabinet	480mm×480mm	Resolution of cabinet	120 ×120
Area of cabinet	0.2304 m <sup>2</sup>	Density of pixel	62500dots/m <sup>2</sup>
Pixel configuration	1R1PG1B	Red wavelength	625±2nm
Green wavelength	525±2nm	Blue wavelength	470±2nm
Colors	68.7billion	Best viewing distance	≥3m
Horizontal viewing angle	140°	Maximum power consumption	< 1100 W / m <sup>2</sup>
Brightness	1200cd/ m <sup>2</sup>	IP grade	IP20
Gray scale	256 levels per color	Color temperature	6500K
Control method	Synchronization	Driving method	Constant 1/16 scanning
Frame frequency	60Hz	Refresh frequency	≥2000Hz
Working voltage	AC220V/110V±10%	Working temperature	0°C-- +45°C
MTBF	More than 10,000 hours	Life span	100,000 hours



GLIC LED Displays Inc/510 Coralridge Pl, Suite 101, City of Industry, Ca 91746

Phone: 626-236-0920 Fax: 626-316-7232 Email: [glic2000@hotmail.com](mailto:glic2000@hotmail.com) Website: [www.generallinkintl.com](http://www.generallinkintl.com)